



Excelsys Technologies Ltd.
27 Eastgate Drive
Eastgate Business Park
Little Island
Co. Cork, Ireland

Tel: + 353 21 4354716
Fax: + 353 21 4354864

DECLARATION OF CONFORMITY

Product Name: UltiMod Series

Product Type: Component Power Supply

Model Number: UXz abcdef g k h j for 6 slot UltiMod powerPac units populated with powerMod modules or
UXz abcd g k h j for 4 slot UltiMod powerPac units populated with powerMod modules

Where:

"UX" = All UltiMod part numbers start with "UX"

"z" = 6, 4, or D

6 = 6 slot UltiMod powerPac

4 = 4 slot UltiMod powerPac

D = 6 slot UltiMod powerPac dual input fused

"a" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"b" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"c" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"d" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"e" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"f" = 0, 1, 2, 3, 4, 5, 6, 7, 8, A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R or T

"g" = '-', P, C, R or S

'-' = Standard model (nominal voltage)

P = Specific voltage adjustment settings

C = Conformal coating

R = Ruggedised for vibration

S = C + R

"k" = Any alphanumeric character describing customer internal wiring lengths. Where no internal wiring exists and standard IEC appliance inlet is used k=0.

"h" = 0, 2, 4 or 6

0 = Standard model

2 = Reverse fan

4 = Low leakage

6 = 2 + 4

"j" = Any alphanumeric character. Optional. Logistics use only.

Excelsys Technologies Ltd. confirms that this product conforms to:

Safety

Safety of Medical Electrical Equipment: EN 60601-1: 1990 / A1: 1993 / A11: 1993 / A12: 1993 / C1: 1994 / A2: 1995 / A13: 1996

Safety of Medical Electrical Equipment: EN 60601-1: 2006 / C1: 2010 / A11: 2011 / A1: 2013 / C2: 2014 / A12: 2014

Supplementary Information

Safety tests were conducted by UL International Demko A/S. By conformance with the standards referenced, the product follows the provisions of EC Directive 2014/35/EU (Low Voltage Directive) with the exception of the enclosure requirement. These products are only for inclusion by professional installers within other equipment and must not be operated as stand alone products.

These power supplies provide REINFORCED INSULATION between input and output and may be used as an SELV circuit or a TNV power source which is insulated from the AC mains.

The maximum ambient temperature must not exceed 40°C at full load.

Place of Issue: Cork, Ireland
Date of Issue: 20th April 2016

For and on behalf of
Excelsys Technologies Limited



Dermot Flynn